



## Programming In Cab Monitor (OZX-TMON)

- 1) Download and Install the latest OZ-X Installer App.
- 2) Open the OZ-X Installer App, in the **Devices** section it will show a list of **DRX110** (monitors) nearby. Press on the nearest device.
- 3) Press **Setup**, then press **Device**.  
*Note: If there is an Update available, please update to latest version first before proceeding with setting up the Monitor.*



OZ-X Installer

- 4) Press the **QR Scan** button and scan the QR code on The Truck's Transceiver Box. (Or manually enter the 12 Digit Truck ID)
- 5) Once entered, press **Confirm** then **OK** once the Configuration succeeded appears. Press the **back** arrow to return to the **Setup** screen (If no other settings changes are required. Otherwise adjust required settings first then press the back arrow).

### Device Settings Options:

**Number of Trailers:** 0 to 7 (This settings allows you to control the number of trailers the monitor can display. Note: The minimum and maximum number of trailers that can be displayed will depend on the Trucks Transceiver configuration settings)

**Pressure Unit:** BAR / PSI - Default PSI

**Temperature Unit:** C / F - Default C

**Audio Alarm:** OFF/ON (Monitor will beep for alarm warnings if ON) - Default OFF

**Sleep Time:** 0 - (Time to which monitor will switch off if the monitor detects no movement for 'x' amount of minutes. Recommended to set to '0')

- 6) Press **Devices**, then press on the connected device to disconnect. Once disconnected, check the monitor to ensure TPMS data is being displayed. App must be disconnected otherwise no data will come through.

